

2024 PRODUCT

CATALOGUE

INDUSTRIAL SOLUTIONS



TABLE OF CONTENTS

ABRASIVES		AEROSOLS	
Cutting and Grinding Discs	1-2	•	23
TCT Saw Blades	3	Gasket Marker	23
Ceramic Grinding Wheels	4	Paintable Acrylic Silicone Sea	alant23
Flap and Sanding Discs	5		
Backing Pads and Wire Brushes	6		
_	7	FLUID HANDLING	
Boiler Brushes	7		
Water Paper	8	Flow Meter	24
•	8	Nozzle	25
	8	Filter	25
•	9-11	Hose	25
•	12	Pump Kits	26
		Drum Pumps	27
		Siphon Hose	27
PPE		Grease Nozzle	27
		Grease Gun Hose	28
	13	Grease Control Valve	28
•	14	Grease Dispensers	29
Wheels	15	orease Dispensers	27
LOCKS		TORCHES	
		Chatliabt	20
Padlocks	16	. 3	30
Mortice Lock	17		
Cylinder Night Latch	17	Spare Batteries and Charger	32
Key Holders	17		
Bullet Hinge	17	ALITOMOTIVE	
Lockable Toggle Latches	17	AUTOMOTIVE	
		Air Compressor	33
KNIVES		Car Diagnostic Apparatus	34
		Battery Tester	34
Folding and Utility Knives	18	Crocodile Clamps	35
		Tyre Chagers	35
TAPES			
		ELECTRICAL	
9 1	19		
11 3 3 1	19	Surge Protectors	36
	19	Surgerrotectors	
• • • • • • • • • • • • • • • • • • •	19		
Cable Ties	20		
SILICONE			
SILIOUNL			
	21		
Multi-Use Spray Paint	22		

..... 22

Cold Zinc



TABLE OF CONTENTS

CUTTING & DRILLING TOOLS

Turning Tools 37-38 **End Mills HSS Annular Cutters** 40 **Burrs** 41-42 SDS Drill Bits43 Chisels44 **Masonary Drill Bits**45 **Auger Bits** 45-46 Bi-Metal Holesaw and Abours47 **HSS Drills Set**48 **HSS Steel Drill Bits**48 Loose Taps and Dies49 Tap Wrench 50 Die Stock50 Morse Tapper Sleeves 51 Center Drill Bits51 Tap and Die Sets 52-53 **Broach Cutters**54 Floor Type Drill Press55 **Grinders**56 Mitre Saws 57-58 Magnetic Base Drills 59-60 **Ratchet Threaders**61 Pipe Threading Machine62

FORESTRY

Ladders	63
Pallet Jacks	64
Chainsaw Chain	65
Chainsaw Guide Bars	65
Chainsaw File	65
Trimmer Line	65

MINI CATALOGUES











BONDED

Abrasives

CUTTING & GRINDING DISC

ACE-CRAFT

Ace-Craft Gold Range high performance wheels will handle virtually any grinding or cutting job. Cutting sheets ,Grinding welds, finishing surfaces, and cutting out auto body parts are perfect applications for these premium grinding discs and cut-off wheels.



CUTTING DISCS FOR HANDHELD MACHINES

- Designed for cutting all grades of metals
- High cutting output with good tool life
- Maximum working speed 80 m/s
- MPA & ISO CERTIFIED







Slimline Inox Cutting Discs

SIZE	SALES UNIT / PACKAGING UNIT
4" 100MM x 1.0 x 16MM	1 pc / Outer box 500 pcs
4,5" 115MM x 1.0 x 22.2MM	1 pc / Tin 10 pcs
9" 230MM x 1.9 x 22.2MM	1 pc / 5 pcs / 50 pcs

^{*} for metal & stainless steel



Standard Metal Cutting Discs

SIZ	E	SALES UNIT / PACKAGING UNIT
4"	100MM x 2.4 x 16MM	1 pc / 10 pcs
4,5	" 115MM x 3.0 x 22.2MM	1 pc / 10 pcs
7"	230MM x 3.0 x 22.2MM	1 pc / 10 pcs
9"	230MM x 3.0 x 22.2MM	1 pc / 10 pcs

* for metal

GRINDING DISCS FOR HANDHELD MACHINES

- Designed for processing all grades of metal.
- High material reemoval with good tool life
- Maximum working speed 80 m/s
- MPA & ISO CERTIFIED







Metal Grinding Discs

SIZE	SALES UNIT / PACKAGING UNIT
4" 100MM x 6.0 x 16MM	1 pc / 10 pcs
4.5" 115MM x 7.0 x 22.2MM	1 pc / 10 pcs
7" 180MM x 7.0 x 22.2MM	1 pc / 10 pcs
9" 230MM x 7.0 x 22.2MM	1 pc / 10 pcs

CUTTING DISCS FOR STATIONARY & SEMI-STATIONARY MACHINES

Ace-Craft Gold Range wheels for use on circular saws and stationary equipment offer you economical, reliable performance in most cutting applications. For fast-cutting action , good service Life and overall performance on chopsaw machines, these general purpose wheels will accomplish your goals.



Standard Cutting Discs

SIZE	SALES UNIT / PACKAGING UNIT
14" 350MM x 3.2 x 25.4MM	1 pc / 10 pcs
350MM x 3.2 x 32.4MM	
16" 400MM x 3.2 x 25.4MM	1 pc / 10 pcs
400MM x 4.0 x 32MM	



Superior quality diamond saw blades with scientifically designed adhesion of the diamond matrix to the steel centers ensure optimum performance with maximum results



Diamond Cutting Segmented Saw Blades

SI	ZE	SALES UNIT / PACKAGING UNIT
4.5"	' 115MM x 10 x 2 x 22.23MM	1 pc
9"	230MM x 10 x 2.8 x 22.3MM	1 pc

* for stone, concrete, steel reinforced concrete, tiles







TCT SAW BLADES FOR WOOD

- · Wide range of uses in wood processing
- For clean cutting results for ripping or cross cutting in softwood and hardwood
- Suitable for hard wood and plywood, untreated chipboards, coated or veneered, MDF, composite materials









DIAMETER	TEETH NUMBER	MAX RPM	BORE
7¼ " (185mm)	T40	8.400 RPM	25.4mm
8¼ " (210mm)	T40	7.200 RPM	25.4mm
10" (250mm)	T40	6.100 RPM	25.4mm
12" (300mm)	T40	5.100 RPM	30mm

TCT SAW BLADES FOR ALUMINIUM

- Perfect cuts in aluminium thanks to special tooth geometry
- Good tool life thanks to carbide quality and finely ground teeth
- Precise, low-noise and vibration-minimised cuts thanks to lasered expansion slots (and partially laser ornaments) as well as lasered steel blades made from sintered steel










DIAMETER	TEETH NUMBER	MAX RPM	BORE
8¼ " (210mm)	T80	7.200 RPM	25.4mm
8½ (216mm)	T80	7.200 RPM	25.4mm
10" (250mm)	T100	6.100 RPM	25.4mm
12" (300mm)	T100	5.100 RPM	30mm



APPLICATIONS

Fine grit (60N): suitable for fine grinding of hardened and unhardened steels, for example spiral drills, screwdrivers, chisels, turning chisels, splitting tools, bevelled-edge chisels, carving knives

Coarse grit (36P): suitable for pre-grinding of hardened and unhardened steels, for example chisels, splitting tools

Aluminium Oxide Wheels (Grey)

Are used for grinding of all materials in a variety of grinding operations ranging from rough sharpening to off-hand grinding or sharpening of tools.

Silicon Carbide Wheel (Green)

Are suitable for grinding hard alloy optical glass, vitrify honing cylinder agate, honing cylinder sleeve and other hard friable materials

ACE-CRAFT

CERAMIC GRINDING WHEELS	GRIT
	A24
	A36
Grinding Wheel 150*25*31.75	A60
	GC36
	GC60
	A24
	A36
Grinding Wheel 200*25*31.75	A60
	GC36
	GC60
	A36
Grinding Wheel 250*40*31.75	A60
Grinding wheet 250 40 31.75	GC36
	GC60

CERAMIC GRINDING WHEELS	GRIT
Grinding Wheel 250*40*50.8	A36
Officiality wheet 230 40 30.0	GC60
Grinding Wheel 300*40*75	A36
	GC60
Grinding wheel 300*40*50.8	A36
ormanig wheet 300 40 30.0	GC60
Grinding Wheel 300*50*50.8	A36
ormanig wheet 300 30 30.0	GC60
Grinding Wheel 350*50*50.8	A36
ormanig wheet 330 30 30.6	GC60

^{*}Other sizes available on request



ASSORTED MOUNTED STONES

used in all foundries, heavy engineering and machine shops, tool rooms and in the construction industry- mounted points are the ideal tool for removing excess material

Application:

Blending tools and dies Deburring Enlarging holes Fettling of castings Available:

Various grit sizes 6mm spindle 5 piece set

COATED

Abrasives



PRODUCT DISCRIPTION	GRIT
7" & 4.5" ZIRCONIA FLAP DISCS	40
7" & 4.5" ZIRCONIA FLAP DISCS	60
7" & 4.5" ZIRCONIA FLAP DISCS	80
7" & 4.5" ZIRCONIA FLAP DISCS	120

PRODUCT DISCRIPTION	GRIT
7" FLAP DISC STANDARD	40
7" FLAP DISC STANDARD	60
7" FLAP DISC STANDARD	80
7" FLAP DISC STANDARD	120

ZIRCONIA FIBRE RESIN DISCS

Very aggressive stock removal on steel, stainless steel and other metal applications, extremely long life, cooler grinding Application:

For universal use

- Metal
- Wood
- Non-ferrous metals

Available in:

115mm & 180mm diameter Various grits sizes



PRODUCT DISCRIPTION	GRIT				
Fiber Disc 180mm Zirconium	D0.4			D00	D400
Fiber Disc 115mm Zirconium	P24	P36	P60	P80	P120

BACKING PAD FOR SANDING DISCS



BACKING PADS, STANDARD

Standard version for medium to rough grinding work To use with filter grinding discs All pads with adjusting nutMaximum working speed 80 m/s $\,$

PRODUCT DISCRIPTION	GRIT
Plastic backing pad for Sanding discs 115mm	115mm
Plastic backing pad for Sanding discs 180mm	180mm

DIAMOND POLISHING PADS



Diamond Polishing Pads ideal for use on Porcelain, Marble, Granite Concrete & Stone and Suitable for polishing Concrete Countertop Surface & Edge, polishing Quartz Granite and Marble Counter Edge and polishing Terrazzo Concrete Floor.

PRODUCT DISCRIPTION	GRIT
DIAMOND POLISHING PADS 100mm	100
DIAMOND POLISHING PADS 100mm	200
DIAMOND POLISHING PADS 100mm	400
DIAMOND POLISHING PADS 100mm	800
DIAMOND POLISHING PADS 100mm	1500
DIAMOND POLISHING PADS 100mm	3000

CRIMPED CUP WIRE BRUSH



STEEL-WIRE CUP BRUSHES, CRIMPED STEEL

For light surface processing and deburring work in all metal processing For processing larger areas, weld seams, metal plates

Edging type: crimped steel wire

PRODUCT DISCRIPTION	MATERIAL
Crimped Wire Brush 75mm	stainless steel
Crimped Wire Brush 100mm	stainless steel

TWISTED CUP WIRE BRUSH



STEEL-WIRE CUP BRUSHES, TWISTED STEEL

For universal use in metal processing, e.g. for cleaning, deburring, purging, removing rust, smoothing welding seams and points, stripping slag, scales and old paint

For processing large areas, weld seams etc.

Edging type: twisted steel wire

PRODUCT DISCRIPTION	MATERIAL
Twisted Cup wire Brush 75mm	stainless steel
Twisted Cup wire Brush 100mm	stainless steel



BENCH GRINDER WIRE WHEEL



Wheel brushes Professional Series Wheel Brushes in highly resistant crimped steel wire and with very high filament density.

PRODUCT DISCRIPTION	MATERIAL
150mm Bench grinder wire wheel	stainless steel
200mm Bench grinder wire wheel	stainless steel

^{*}For use on Bench Grinders

BOILER BRUSH


Ace Craft Boiler Tube Brushes are mainly used in pipe and boiler tube cleaning and flue cleaning. Extension rods are available for purchase to help reach long and deep pipes, or even chimneys.

These tube brushes can also be used in chimney cleaning and maintenance, making them the perfect chimney brushes.



PRODUCT DISCRIPTION	MATERIAL
Boiler brush 2"	zinc cated
Boiler brush 2.25"	zinc cated
Boiler brush 2.5"	zinc coated
Boiler brush 2.75"	zinc coated
Boiler brush 3"	Zinc cated

WIRE BRUSH BLUE HANDLE ACE-CRAFT





WATER PAPER **ABRASIVES** COATED

WATER PROOF ABRASIVE PAPER

PROPERTIES

- SiCa Mineral
- Resin over Resin
- Closed Coat
- C-Weight Paper
- Waterproof

CHARACTERISTICS

- Pliable waterproof Latex Backing allows for great flexibility while maintaining good stability
- Polish of sensitive areas
- Low removal rate
- Very long life
- · Very good surface finish

APPLICATIONS

- Composites
- Automotive
- -Steel
- -Paint & Fillers
- -Varnish
- -Wood



GRIT	80	120	180	240	320	400
GKII	600	800	1000	1200	1500	

ANTI-CLOGGING SAND PAPER

Properties

- Al Oxide mineral
- Resin over Resin
- Semi-Open Coat
- B-Weight Paper
- · Stearated for anti-clogg

Characteristics

- Consistent scratch pattern
- Reduced loading
- Flexible backing
- Medium removal rate
- Excellent surface finish

Application

- Woodworking
- Composites
- Automotive
- Paint/ Varnish & Fillers



SIZE	GRIT
230*280mm	80
	120
	180
	240
	320
	400
	600

Abrasives

EMERY TAPE

EMERY TAPE ROLLS

- Al Oxide
- Resin over Resin
- J-Weight Cloth
- Closed Coat
- Medium Removal Rate
- Long Life
- Good Finishg
- Stainless Steel

Application

- Hand sanding
- Metal-working
- Stainless steel



SIZE	GRIT
	40
50mm * 50 M	60
	80
	120
	150
	220



WIDE CLOTH BELTS

WIDE BELTS RKX0

PROPERTIES

- Al Oxide
- Resin over Resin
- X-Weight Cloth
- Closed Coat

CHARACTERISTICS

- · Very High Removal Rate
- Long Life
- Medium Rough Finish



Size: Custom Grit: R36 - P220

Application

- Calibrating Wood
- Stainless Steel
- Aluminium

WIDE BELTS 102XY

PROPERTIES

- Zirconia/Al Oxide
- Resin over Resin
- Y-Weight Polycloth
- Closed Coat

CHARACTERISTICS

- Very High Removal Rate
- Long Life
- Rough Finish
- Waterproof



Size: Custom Grit: P24 - P150

Application

- Hard wood calibration
- Stainless Steel
- Non-Ferrous Metals

NARROW BELTS











BELT	PROPERTIES	CHARACTERISTICS	APPLICATIONS	GRIT
	Al Oxide	High removal rate	Woodworking	P40 - P240
	Resin over Resin	Long Life	Leather	
NARROW BELTS 1000F	F-Weight Backing	Reduced loading		
	Open Coat	Finish rough to good		
	Anti-Static			
	Al Oxide	High removal rate	Calibrating Wood	P36 - P220
	Resin over Resin	Long Life	Stainless Steel	
NARROW BELTS RKXO	X-Weight Cloth	Medium - Rough Finish	Aluminium	
	Closed Coat			
	Al Oxide	Medium Removal Rate	High Gloss Lacquers and Paint	P400 - P1500
	Resin over Resin	Long Life	Sensitive surfaces	
NARROW BELTS EKA-FILM	Polyester Film	Super Fine and High	Stainless Steel Polishing	
	Semi-Open Coat	Gloss Finish		
	Stearated	Waterproof		
	Al Oxide	Medium Removal Rate	Sanding intricate shapes	P60 - P320
	Resin over Resin	Long Life	Hand sanding	
NARROW BELTS EKA-FLEX	Flex J-Weight Cloth	Good Finish	Light Metal sanding and polishing	
	Semi-Open Coat			
	Zirconia/Al Oxide	Very High Removal Rate	Hard wood calibration	P24-P150
NARROW BELTS	Resin over Resin	Long Life	Stainless Steel	
102XY	Y-Weight Polycloth	Rough Finish	Non-Ferrous Metals	
	Closed Coat	Waterproof	Cast Iron	

*made to order





WIDE SANDPAPER BELTS

BELT	PROPERTIES	CHARACTERISTICS	APPLICATIONS	GRIT
	Al Oxide	High removal rate	Woodworking	P40 - P240
	Resin over Resin	Long Life	Leather	
VIDE BELTS 1000F	F-Weight Backing	Reduced loading		
	Open Coat	Finish rough to good		
	Anti-Static			
	Al Oxide	High removal rate	Woodworking	P40 - P100
	Resin over Resin	Very Long Life		
/IDE BELTS ARKFEO	F-Weight Backing	Highly reduced loading		
	Extra Open Coat	Rough finish		
	Anti-Static			
	Al Oxide	Medium removal rate	Woodworking	P120 - P180
	Resin over Resin	Very Long Life	Veneer	
VIDE BELTS ARKFO	F-Weight Backing	Reduced loading		
	Open Coat	Good finish		
	Super Anti-Static			P120 - P180F P120 - P180F
	Si Carbide	Low removal rate	Woodworking	P120 - P180F
	F-Weight Backing	Long Life	Stainless Steel	
WIDE BELTS ARSFO	Open Coat	Reduced loading	Sheet and coil metals	
	Anti-Static	Very Good finish		
	Resin over Resin			
	Si Carbide	Low removal rate	Staines surfaces and lacquer	P240 - P1000
	Resin over Resin	Very Long Life	Leather and textiles	
VIDE BELTS AESM	E-Weight Backing	Reduced loading	Rubber	
VIDE BEETS AESIM	Semi-Open Coat	Very Good finish		
	Anti-Static			
	Stearated			
	Si Carbide	Medium removal rate	Especially suited to hard lacquers	P240 - P600
	Resin over Resin	Long Life		
VIDE BELTS AESMNS	E-Weight Backing	Reduced loading		
	Semi-Open Coat	Good finish		
	Anti-Static			

^{*}made to order





SANDING BELT

We recommend that you make sure of the exact size required for the belt sander as per its specifications. The belt may slip if it is too long or break if it is too short. A belt that is too short will cause extreme load on the bearings/bushings, shortening the machine's lifespan.



SIZE	GRIT
	60#
100*610mm	80#
	120#
	60#
75*533mm	80#
	120#

NON- WOVEN SANDING PADS

Excellent finishing on a range of metals Rust and loading resistant Can be used wet or dryLow heat - no work piece discolouration

- Conformable and long lasting
- Very low stock removal
- Protect surface against corrosion
- Reduced loading
- Metalworking
- Stainless Steel
- Automotive



SIZE 150*230mm

FLAP WHEEL

Small abrasive mop with fan shaped abrasive flaps securely fixed to a mounting spindle. Available in 6mm spindle

Ideal for grinding small parts and castings.

Grinding of internal surfaces on pipes, fittings and difficult to reach areas. Finishing of work pieces with profiles and detail.

Flap wheels can be mounted onto straight grinders, flexible shaft grinders and drilling machine



SIZE	GRIT
40 X 25 X 6MM	
50 X 35 X 6MM	60
60 X 40 X 6MM	



ABRASIVE MESH

With Ace- Craft Dust free sanding Mesh, there has been a success of developing a completely even sanding net. Its thousands of holes provide for easy dust extraction. The maximum distance from each sanding particle to the closest dust extraction hole is just 0.5 mm.


Advantages:

Using Ace-Craft Dust free sanding mesh, dust is removed from the space between the abrasive and the sanded surface, which means that the abrasive grains are cutting the surface more efficiently, as they remain unhibited by dust particles.

Because the dust is being continuously sucked away, sanding is virtually dust-free. Keeping the abrasive and the sanding surface constantly dust-free extends the lifespan of the abrasive.

Since the abrasive maintains its aggressive properties over the entire surface, sanding becomes more even and efficient, improving the quality of work. Since you can always see what is being sanded, you gain excellent control over the work to avoid over-sanding, for example.

Ace-Craft Dust free sanding mesh solves many problems, such as the formation of so-called dust pills and clogging. Because dust no longer collects in lumps on the sanding discs to the same extent as before, there is no danger of sanded dust building up



TOOL	SIZE	
Abrasive Mesh	150mm	80
Abrasive Mesh	150mm	120
Abrasive Mesh	150mm	180
Abrasive Mesh	150mm	240
Abrasive Mesh	150mm	320
Abrasive Mesh	150mm	400



TOOL	SIZE	
Abrasive Mesh	70x198mm	120
Abrasive Mesh	70x198mm	180
Abrasive Mesh	70x198mm	240
Abrasive Mesh	70x198mm	320
Abrasive Mesh	70x198mm	400
Abrasive Mesh	70x420mm	120
Abrasive Mesh	70x420mm	180
Abrasive Mesh	70x420mm	240
Abrasive Mesh	70x420mm	320
Abrasive Mesh	70x420mm	400

The abrasives product is one-piece fabric which has construction of net design and loop. It provides open mesh construction and excellent dust extraction ability. Coating with Aluminium Oxide provide well cutting ability. Due to no clogging and special coating, this product performs good cutting power and life span.

Application: Automotive industry, Automotive Aftermarket and Furniture industry.

Available dimension: Jumbo roll and any Dimension

Available Girt: #60~#2000

VELCRO



Industrial Coated Gloves

The specially formulated lunar porous finish allows moisture and oil to be conducted away from the surface for much improved grip in wet and oily conditions.



LIQUID REPELLENT

- Full, double dip for fluid/water resistance
- Latex Palm Coated, Smooth Finish
- Crinkle Finish for Super Grip
- Hi-vis color on back-of-hand enhances
 visibility and compliance
- High dexterity and superior comfort





Available with Anti-Fog coating Available with Anti-Scratch coating Provide 99.9% protection against harmful UV rays.









Design for full eye protection with integrated side shields.

Flexible rubber nose pad for a comfortable fit and reducing pressure point for all-day iob.

Brow guard helps to deflects airborne particles.

Extended lens provides excellent side protection.

Modern & classic design, for use in mining and industrial area or on-site work.



•Clear

•Smoke Lens









Extremely popular design.

Lightweight and design for all around impact protection.

Extremely durability and flexible temples provide a secure fit and all-day comfort.

Good fit for both smaller and larger faces due to contour design and flexibility of frame.

Available Lens Color

•Clear

•Smile

Yellow Lens







Visitor safety glass with a large frame to be used alone, or over-the-glass style to suit all your tasks.

Molded nose bridge design to fit most ofusers. Could be worn itself as a safety glass or able to fit over prescription glass.

Non-slip temple design.

Available Lens Color

Clear

•Over spectacle







Indirect vent anti-fog goggles.

Lightweight and extremely durable.

Individually packed for convenience.

Suitable for protection from average speed impact and liquid splashes as well as large dust particles.

Available Lens Color

•Clear

·One size







WHEELS



RUBBER	CASTER			
0	91		•	kg
11075RR	75x22	30	12	40
11075RR	85x24	30	12	50
11100RR	100x26	40	12	60
11125RR	125x33	40	15	100
11150RR	150x39	40	20	110
11160RR	160x39	40	20	130
111200RR	200x44	40	20/25	150
111250RR	200x44	40	20/25	130
111250RR	250x44	55	20/25	180
111300RR	300x57	60	25	200




EUROPEAN TYPE ELASTIC RUBBER CASTER									
7		V	U;	⊘	U		kg		
46080BL	46080BLF	46080BLB	105	80x35	31	102x80	60		
46100BL	46100BF	46100BLB	128	100x35	33	102x80	80		
46125BL	46125BLF	46125BLB	155	125x35	35	102x80	110		
46160BL	46160BLF	46160BLB	195	160x35	45	135x110	150		
46200BL	46200BLF	46200BLB	240	200x50	47	135x110	170		



RUBBER CASTER						
7	T;	⊘				kg
24025F	36	25x14	37x19	29	4	10
24030F	41	30x14	37x19	29	4	15
24040F	50	40x17	48x25	35x15	4	20
24065F	84	50x22	60x11	44x24	6	25
24075F	82	65x23	70x44	53x27	8	30
24075F	91	75x25	70x44	53x27	8	40









HEAVY D	UTY BR	RASS PA	ADLOC	KS					
ART.NO	Α	В	С	D	E	F	G	н	weight (g)
261	21	19.5	10.7	10.7	33.5	33.5	10.4	6	33.5
262	25	24.5	12.6	12.6	4.4	41.5	11.5	7	53.5
263	32	29.6	16.6	16.6	5.4	51.6	14	8.5	96.5
264	38	34.6	19.6	19.6	6.4	60.6	15.6	9.5	145
265	50	42.6	25.2	25.2	8.8	76.5	18.4	11.5	285
266	63	52	32.2	32.2	10.8	95	21.6	13	520
267	75	60	40.5	37.8	12.2	112.97	25	15	820
L265	25	24.5	47.5	12.6	4.4	76.4	11.5	7	62
L263	32	29.6	57.2	16.6	5.4	92.2	14	8.5	111
L264	38	34.6	67.6	19.6	6.4	108.6	15.6	9.5	168
L265	50	42.6	75.1	25.2	8.8	126.5	18.4	11.5	333

HEAVY DUTY BRASS

ACE CRAFT 3 LEVER LOCKSET - SATIN CHROME



FEATURE AND BENEFITS

- 3 lever lockset.
- Chrome plated zinc handles.
- Chrome plated cast zinc backplate.
- Use on internal doors only, high level of security.
- Powder Coated Lock Body.
- Two Zinc Keys
- Durable for long life operation.
- Fit left or right hinged doors.

ACE CRAFT - NIGHT LATCH CYLINDER



FEATURE AND BENEFITS

- Slam lock latch.
- Can be deadlocked from the inside.
- Latch can be held back in open position.
- Suitable as secondary security device on external doors.
- Anti credit card feature.
- Die cast body.



KEY HOLDER




FEATURE AND BENEFITS

Tag and track your keys with Ace Craft Key Tag Holders.

BULLET HINGE








KNIVES









MASKING TAPE HIGH TEMP



MASKING TAPE SOLVENT MSK 9410 WATER RESISTANT 120° It serves as a shielding purpose for car painting in the automotive refinishing industry. It is generally used in the baking process of the automotive refinishing industry, aerospace industry, marine industry and electric appliances for fixing protection. It has good protection performance when used in the high-temperature process because it can endure a higher level of temperature to medium temperature.

SPECS 18mm*40M yellow 24mm*40M yellow

BOPP PACKING TAPE



Buff tape resembles the natural color of the carton, so when you apply the tape on the box, it will give you a uniform color throughout carton. Buff tape is mainly used to seal boxes by hand or through carton sealing machine.

Measurements: 48mm x 50M

SPECS 48mm*50M Brown

PTFE THREAD TAPE



Thread Seal Tape to seal threaded joints on metal or plastic pipe fittings. This tape is made to wrap around threading to help create a watertight barrier. Use to seal threaded joints on metal or plastic pipe fittings

Helps prevent leaks Wrap around threading to create a watertight barrier White color For outdoor use and cold water only

SPECS 12mm*10M

FLAME RETARDANT PREMIUM ELECTRICAL TAPE



Vinyl Electrical Tape is a premium grade, all weather tape that is designed to provide a protective jacket and primary electrical insulation for splices up to 600V. The flame retardant tape withstands a high temperature of up-to 80V.





CABLE TIES

FEATURES


Ace Craft cable ties are suitable for bundling and securing cables, pipes and hoses. The innovative and effective cable ties enable a simple and quick installation.

- Weather-resistant black cable tie available in a wide range of sizes.
- Open lock head for quick and easy insertion
- Integrated pre-locking function
- Inside serration for a strong hold around bundles
- Easy application either manually or with a processing tool
- UV-resistant Certification & Approvals

APPLICATION

Our cable ties are suitable for the following markets and industries:

- Automotive Industry
- Electrical Installation
- Electronics Industry
- Industrial Automation
- OEM Industry
- Panel Building
- Solar Energy Sector
- Telecommunications
- Wire Peocessing





WD-40 Multi-Use

MULTIFUNCTION LUBRICANT

WD-40 Multi-Use Product protects metal from rust and corrosion, penetrates stuck parts, displaces moisture and lubricates almost anything.



CLEANS & PROTECTS



DRIVE OUT MOISTURE



CORROSION INHIBITOR



LOOSENS RUSTED PARTS



- Stops Squeaks
- Drives Out Moisture
- Cleans and Protects
- Loosens Rusted Parts
- Frees Sticky Mechanisms

SEE CAUTIONS ON REVERSE

400 ml

Silicone Free

Multi-Use Spray Paint

SPRAY PAINT

Our paint is made from 100 % Acrylic resin and CFC free and used advanced technology. It has excellent hardness with excellent weather resistance, rich color and glossy finish.



FAST DRYING



RUST RESISTANT

TECHNICAL DETAILS

19.6 x 6.5 x 6.4 cm Package Dimensions: Item Volume: 400 Milliliters Finish Type: Flat **Included Components:** Spray Black Red Green Gold White ____ Yellow Silver Blue **Cold Galvanizing**









GENERAL PURPOSE SILICONE



9	- 19
	Q.Q.Q
LICONE SEALA	The second secon
	Digital research

PRODUCT DISCRIPTION	SPECS
GP Silicone Sealant 300ml	CLEAR
GP Silicone Sealant 300ml	WHITE
GP Silicone Sealant 300ml	BLACK



WHITE **CLEAR**

BLACK

BROWN

*Cannot be painted

PURE-BOND GASKET MAKER





85 gram hand tube PURE-BULL 310ml Tube







300ML PAINTABLE ACRYLIC SILCIONE SEALANT

- Temperature resistance -20°C until +80°C once fully cured - Can be painted with all types of paint - Do not apply when rain or frost is imminent



Έ	CS			

300ML Paintable Acrylic Silicone Sealant

WHITE

BLACK [

CLEAR

BROWN [

CAULKING GUN (YS-104)

- Do not expose packaging to frost

High quality manual applicator gun for the application of 310 and 400ml cartridges of acrylics, silicones, Gasket Makers and adhesives.

Ergonomic Handle Strong & Robust







FEATURES

- · Bursting Pressure 28 Bar
- · 3 Digit Display
- · Easy Calibrate
- 4 Flow Directions
- · Non-commercial Use
- · Connection: 25mm (1" Internal Thread)
- · Mounting: Vertical Or Horizontal
- · Subtotal Reset Function

Suitable For Gravity-fed And Pumped Systems



The Ace Craft A33 is an oval gear mechanical meter engineered for an accurate measuring of the quantity of fluid dispensed that meets international standard requirements . Reliable and easy to install, it can be calibrated on site and simply fitted with both rigid or flexible pipes or can be put directly on pumps or gravity feed tanks.

PERFORMANCE

20-120 L/MIN FLOW-RATE





DETAILS







MATERIALS

Body: Aluminium

Nutating Disk Chamber: Technopolymer

TECHNICAL DATA							
	FLUIDS TYPE	DIRECTION	FLOW-RATE		PRESSURE		
DESCRIPTION			L/MIN	GPM	BAR	PSI	INLET / OUTLET
A33-VER. A	0	+	20 - 120	5 - 32	3,5	50	1" BSP
A33-VER. B	0	A	20 - 120	5 - 32	3,5	50	1" BSP
A33-VER. C	0	₩	20 - 120	5 - 32	3,5	50	1º BSP
A33-VER. D	0	→	20 - 120	5 - 32	3,5	50	1" BSP




MANUAL NOZZLE

FEATURES

- Manual
- Versatile
- · High Efficiency
- Lever protection
- · Light weight
- · Aluminium Material



The Ace Craft manual nozzles perform the maximum efficiency thanks to the low-flow resistance and the wide range of applications including transfer systems run by gravity.





		FLOW-RATE		INLET	SPOUT
DESCRIPTION	FLUIDS TYPE	L/MIN	GPM	Ø BSP	EXT. Ø MM
SELF 2000 1"	D	120	32	1" BSP	25

FEATURES

- Bursting pressure 10 bar
- · Replaceable cartridge
- · High efficiency
- small

OIL AND FUEL FILTER




ACE-CRAFT

Fuel Filter

DETAILS







DESCRIPTION			FLOW-RATE		WATER	EFFICIENCY	MICRO	PRESSURE
	FLUIDS TYPE	L/MIN	GPM	Ø BSP	ABSORBING	β	m	BAR
100 L/MIN FILTER WITH HEAD	D	100	26.4	1"	NO	2	10	12

FEATURES

· Diameter : 1"

· Length : 6m, 4m

· Material : Rubber

ACE-CRAFT NEI IVERY HUSE

The delivery hose is reinforced with steel webbing and it comes complete with fittings. Custom length hoses available to order.







BATTERY KIT (12 VOLT)

FEATURES

- Versatility
- · Mobile and ready to use
- On/off switch



The Ace Craft Battery Kit is a portable transfer unit with a self-priming electric vane pump. Its modular composition allows users to have different pumps according to the required flow-rates and different applications. It is equipped with a fixed brush motor with permanent magnet stator and terminal board with switches and fuses to protect against overload. It is always supplied with an integrated nozzle and a set of accessories.

PERFORMANCE



30 MIN

DUTY CICLE







IN THE BOX

- · Pump
- · Suction hose
- · Delivery hose
- · Handle
- · Nozzle
- · Mesh filter and connections
- Cables
- · Instruction manual
- · Steel Mounting Board

DETAILS







ACE-CRAFT

FEATURES

- Features
- · Ready to use
- Easy to install
- · Sturdy structure
- · High precision meter
- · Available with different
- pumps

220 VOLT KIT

The Ace Craft 220volt Diesel pump and Meter kit is a diesel transfer station for fixed installations composed of AC pump, nozzle, and A33 flow meter for safe and controlled refueling operations. Easy to install, this station can be used to fill mobile tanks or interact with distribution units.

PERFORMANCE









IN THE BOX

- · Pump
- · Suction hose
- · Delivery hose
- · Handle
- · Nozzle
- · Mesh filter and connections
- Cables
- · Instruction manual
- · Steel Mounting Board




ROTHRY PUMP

FEATURES

- · Galvanized iron spout and suction pipe prevents oxidation
- Variable-length 3 part rigid suction pipe
- Durable wooden handle
- · Sturdy Connector Fits all standard 200L drums
- Suitable for use with Diesel and oil

THE ACE CRAFT CAST IRON ROTARY HAND FUEL PUMP



These rotary vane type hand fuel transfer pumps are a popular choice for transferring fuel when cost-effectiveness is important, when only small quantities need to be dispensed at a time, or when no mains power is easily available.

This manual diesel transfer pump is supplied with a 2" M BSP drum adaptor and a three-part rigid suction downtube.



SIPHON HOSE

How to use:

- 1. Before using, drain all liquid from the hose.
- 2. The end of the tube must be lower than the pump before siphoning will start.
- 3. Submerge pump into the liquid that is to be siphoned.
- 4. Move pump vigorously in an up and down motion. The pump must remain in the liquid at all times to start the siphoning. Once the flow starts, stop moving or shaking the pump as gravity will maintain the flow of the liquid. Once siphoning starts, keep the pump submerged in liquid.
- 5. To stop siphoning, remove the pump from the liquid.
- 6. Drain all liquid from the hose and clean thoroughly.

PRODUCT DESCRIPTION	DIAMETER
Siphon hose	Small, 1/2"
Siphon hose	Large, 3/4"

FEATURES

- Available in 1/2" Inner Diameter and 3/4" Inner Diameter
- 100% Pure, Lead-Free Copper Pump With An Industrial-Strength Glass Ball And Stainless Steel Spring
- Makes A Great Sump Pump Backup and Emergency Item
- High Quality 100% Virgin Grade Tubing Rated very well for fuel & FDA sanctioned as food grade
- Can be used for Draining Water in areas Without Pumping or Electricity



FEATURES

Spring Loaded Activation Trigger

- Simply depress the trigger when locking the coupler onto the Zerk or to release the coupler when done.
- Easy clip-off, regardless of pressure build up in the line . NO MORE stuck couplers.
- No need to hold while greasing. Lock-on and free up both hands to operate your grease gun.

Sliding Sleeve Locks the coupler onto the Zerk. When you pump grease ... it stays on!



%" NPT Female Thread
Standard size, fits most grease guns.

ACE-CRAFT

GREASE GUN COUPLER



Four hardened spring steel jaws
Resilient under high pressure
Fits all DIN and SAE specification Zerk

Leak Fre High Pressure Seal Patented design reduces leakage



GRERSE COUPLER

FEATURES

- · For use with most Hand-operated Grease Guns and
- · Air-Powered Equipment
- · Fits all 1/8" NPT threads
- · 4500 PSI (310 Bar) Maximum Operating Pressure
- · Built-in Spring-loaded Ball Check Valve prevents Leak,
- · Pressure Loss Lubricant backup
- · Precision fit. Slight pushing action snaps Jaws onto fittings
- · Small outside diameter permits easy contact with recessed
- Fittings
- Zinc Plates for Maximum Protection against Corrosion.

STANDARD GREASE COUPLER, 1/8" NPT

For use with most Hand-operated Grease Guns and Air-Powered Equipment Fits all 1/8" NPT threads 4500 PSI (310 Bar) Maximum Operating Pressure Built-in Spring-loaded Ball Check Valve prevents Leak, Pressure Loss, and Lubricant backup Precision fit.

GREASE GUN HOSE

30CM GREASE GUN HOSE

For use with most Hand-operated Grease Guns and Air-Powered Equipment Fits all 1/8" NPT threads 4500 PSI (310 Bar) Maximum Operating Pressure Built-in Spring-loaded Ball Check Valve prevents Leak, Pressure Loss, and Lubricant backup Precision fit.



FEATURES

- 30 cm
- Maximum Working Pressure 3,000 PSI
- 1/8 In. NPT Male Threads
- · Hand Operated Gun Only

FEATURES


SPECIFICATION	2M GREASE GUN HOSE	4M GREASE GUN HOSE
Length	2m	4m
NPT Threads	1/4″	1/4″
Pressure	3260PSI / 225BAR	7500PSI / 517BAR

HIGH PRESSURE 2M & 4M GREASE GUN HOSE

Slight pushing action snaps Jaws onto fittings Small outside diameter permits easy contact with recessed Fittings Knurled Body and easy flats for Easy Installation and Removal Zinc Plated for Maximum Protection against Corrosion.



GREASE CONTROL VALVE



FEATURES

- 7,500 psi maximum operating pressure
- Balanced design reduces user fatigue
- Lubricant inlet 1/4" NPT(f); outlet 1/8" NPT(f)
- Knurled handle for positive grip
- Precision-machined, all steel handle, body and guard bracket



GRERSE DISPENSERS

GZ-8 PNEUMATIC GREASE PUMP



- Grease out: 0.85 gram / minute
- Pressure transmission: 30-40MPa
- Tank: 12L
- High-pressure hydraulic pipe: 4m
- Weight: 17KG

GZ-A9 PNEUMATIC GREASE DISPENSER



- Grease out: 850 gram / minute
- Pressure transmission: 30-40MPa
- -Tank: 45L
- High-pressure hydraulic pipe: 6m
- Weight: 19/21KG

GZ-6S MANUAL GREASER TROLLEY




- Grease out : 0.5gram/times
- Pressure transmission: 200-250 bar
- Tank : 12L
- High-pressure hydraulic pipe: 2.5m
- Weight: 10kg

GZ-6J FOOT-OPERATED GREASER TROLLEY



- Grease out : 0.5gram/times
- Pressure transmission: 200-250 bar
- Tank : 12L
- High-pressure hydraulic pipe : 2.5m
- Weight: 15kg



ACT2161



Rechargeable 1 Watt LED Spotlight

- * Super bright 1 Watt LED spotlight
- * Two brightness settings High: 4h at 90 lumens Low: 9h at 40 lumens
- * Battery: lead-acid battery (700mAh)
- * Dual recharge : AC/DC charger, 12V DC car plug charger (both included)
- * Size: 160 x 102 x 122mm

ACT2128A



Solar Rechargeable 5W CREE LED Spotlight

- * Suoper bright 5W CREE LED spotlight
- * Two positions of handle to ensure comfortable and ergonomic access
- * Detachable solar charging base
- * Swivel stand
- * Battery: Li-ion 3.7V 4000mAh
- * Over charge, over discharge, over current protection
- * Brightness mode: 360 lumens; 5 hours
- * 3 ways rechargeable : solar cell panel, AC/DC charger, 12V car plug charger (all included)
- * Size: 170 x 160 x 130mm





Light source: ZT 3535 + COB Theoretical brightness: 500 lm Brightness: 200 lumens

Power: 5w Weight: 104g

Material: Aluminium alloy Size: 140*21*21 mm


Power source: 1*14500 rechargeable Li-ion battery

Runtime: 2-5 hours Distance: 100 meters Modes: 5 modes

(strong light>weak light>white COB light>red COB light>red COB light strobe)

Full set: flashlight (with built-in battery)+ box

FLASHLIGHT C8-S



USB flashlight

light source : Luminus SST-40 -W

Brightness :1100lumens

Power :10w

Material:6061-T6 aviation aluminum

Size :155mm*45mm*23mm

Net weight :150g

Power source :1*18650 rechargeable Li-ion battery

Runtime :2-5 hours
Distance :100-200meters

Waterproof :waterproof in daily life

Modes:5modes

(High>Middle>Low>Strobe>SOS)

Full set: flashlight +1*18650 battery+USB cable+green rope+black box.

HEADLAMP



Light source: XDLED Material: ABS

Power 2W

Brightness: 100 lumens Waterproof: IP44 Charging time: 1.5H

Runtime: 3.5H

Distance: 55 meters

Battery capacity: 702535 / 500mAh

Modes: 5 modes

White light: High > Middle > Low

Red light: Light > SO Size: 61*31*34 Net weight: 47g

Long-Lasting Reliabilty

With a ten year shelf life, these batteries are ready for any occasion.

Leakage Protection

Designed with Powerseal Technology to protect from leakage.

DETRILS

1.5V AA Alkaline

1.5V AAA Alkaline

1.5V D Size Alkaline

9V Alkaline

4 PACK

4 PACK

2 PACK

1 PACK



18650 BATTERY



CHARGER AC16



3V LITHIUM COIN BATTERY



Specifications: 18650 lithium rechargeable battery

(PCB protected)

Capacity: 2000mAh

Charging voltage: 4.2V

Output voltage: 3.7V

Weight: 60g

USB Charger

Input: DC 5V 2A (Max)

Output: DC 5V 1A

Size: 125*64*40mm

Output Interface : USB

Codes: CR1616, CR1620, CR1632, CR2016, CR2025, CR2032

High and stable voltage: 3V

Continuous Standard Drain: 0.2mA

HD47L-1-24L

Model No: HD47L-1

Motor: 1.5 KW/2 HP Air Delivery: 0.12m /min Pressure: 700 Kpa

> Tank: 24 L G. Weight: 27 KG

Dimentions: $60 \times 31 \times 58 \text{ cm}$



ACCOMP100

Model No: ACCOMP100

Motor: 1.5 KW/2 HP Air Delivery: 0.12m /min

Pressure: 700 Kpa Tank: 100 L G. Weight: 47 KG

Dimentions: $60 \times 31 \times 58 \text{ cm}$



ACCOMP200

Model No: ACCOMP200 Motor: 2.2 KW/3 HP Air Delivery: 200L/Mi

Pressure: 700Kpa
Tank: 200L

G. Weight: 115 KG

Dimentions: 103 X 49 X 136cm



CAR DIAGNOSTIC APPARATUS



- Support:XP WIN7 WIN8 WIN10; Support online upgrade system and print failure data
- 2.4" TFT color screen
- Detect 12V gasoline and diesel vehicle (can detect battery voltage)
- 2color:black and red

- Support: XP WIN7 WIN8 WIN10; Support online upgrade system and print failure data
- 2.8" TFT color screen
- Detect 12V gasoline vehicle (can detect battery
- voltage)

2color: black and red

BATTERY TESTER





Battery test

12V/ 24V

CROCODILE CLAMPS



SPECIFICATIONS

Current (A) 500







TYRE CHANGER

Dual Assist Arm Wheel Clamp Tyre Changer
PL-1298IT Dual Assist Arm Wheel Clamp Tyre Changer
Suitable for cars, motorcycles and light truck, BMW 7 series.
The PL-1298IT is our professional tire dealer or large car
dealership dual assist arm tilt back wheel clamp tyre changer.

External locking rim dimensions	12-26"
Internal locking rim dimensions	14~28"
Max.Wheel diameter	1143 mm(45")
Max.Wheel width	406 mm(16")
Working Pressure	8-10 bar(116-145 PSI)
Opitonal Power supply	110 V (1 ph)/ 220 V (1 ph/3 ph)/ 380 V (3 ph)
Optional Mottor power	0.55/0.75/1.1 kw
Noise Level	<75 dB
Dimension(main body)	1130*900*1050 mm(3.7*3.0*3.4 ft)
N/G weight(main body)	254/310 kg(559/682 lbs)

4 WAY SURGE PROTECTOR




3 WAY SURGE PROTECTOR

- USB OUTPUT: 3.4A MAX
- RATED POWER: 13A 2500W
- LIGHT METHOD: MASTER SWITCH
- 5USB
- 3USB + 2USB-C
- with independent master switch
- overload protection
- current stability
- 750°C high flame retardant
- child safety protection door




TURNING TOOLS



75° Approach Straight Turning Tool - DIN 4971-IS01


Style 110


CODE	DESCRIPTION	GRADE			IENSIO	INS	
1			а	b	L	С	d
BT245-D002		P25	10	10	90	4	0.2
BT245-D004	Right Hand Cutting	P25	12	12	100	5	0.4
BT245-D006		P25	16	16	110	6	0.4
BT245-D008		P25	20	20	125	8	0.8
BT245-D010		P25	25	25	140	10	0.8
BT245-C008		P25	20	20	125	8	0.8
BT245-C010		K10	25	25	140	10	0.8



45° Approach Straight Turning Tool - DIN 4972-IS02

Style 111






Offset Corner Cutting Tool - DIN4978 - ISO3

Style 115


0005	DECODIDATION	CDARE		DIN	MENSIC	NS	7	
CODE	DESCRIPTION	GRADE	a	b	L	С	d	
BT245-D074		P25	10	10	90	6	0.2	
BT245-D076	Right Hand Cutting	P25	12	12	100	7	0.4	40
BT245-D078		P25	16	16	110	8	0.4	



Recessing Tool - DIN4976 - ISO4

Style 127


CODE	DESCRIPTION	GRADE		DIM	ENSI0	NS
CODE	DESCRIPTION	GRADE	а	b + b1	L	d
BT245-D014		P25	10	10	90	0.4
BT245-D016	Right Hand Cutting	P25	12	12	100	0.4
BT245-D018		P25	16	16	110	0.4
BT245-D020		P25	20	20	125	0.4
BT245-D022		P25	25	25	140	0.4



Offset Side Tool - DIN4980 -IS06


Style 117


CODE	DESCRIPTION	GRADE		DIN	MENSIO	NS	
CODE	DESCRIPTION	GRADE	a	b	L	С	d
BT245-C088		K10	20	20	125	8	0.8
BT245-D090	Right Hand Cutting	P25	25	25	130		
BT245-D069	ragileriana batting	P25	25	25	140	10	0.8
BT245-D090		P25	25	25	140	10	0.8
BT245-D067		P25	20	20	120		
BT245-C069	Left Hand Cutting	P25	25	25	140	10	0.8
BT245-C067		K10	20	20	120		
BT245-D086	Right Hand Cutting	P25	16	16	110	6	0.4
BT245-B065	Left Hand Cutting	P25	16	16	110	6	0.4
BT245-D088	Right Hand Cutting	P25	20	20	125	8	0.8
CONTRACT OF							



Parting Tool - DIN4981 - IS07

Style 150






Intend Boring Bar - DIN4974 - ISO9

Style 136


CODE		DESCRIPTION	GRADE		DIM	MENSIO	NS	
0002	74.3	DESCRIPTION	OKADL	а	b	L	С	d
BT245-D0	042		P25	10	10	150	4	02
BT245-D0	044	Right Hand Cutting	P25	12	12	180	5	0.2
BT245-D0	046		P25	16	16	210	6	0.2
BT245-D0	048		P25	20	20	250	8	0.4
BT245-D0	050		P25	25	25	300	10	0.4
BT245-C0	046		P25	16	16	210	6	0.2
BT245-C0	048		K10	20	20	250	8	0.4
BT245-D0	050		P25	25	25	300	10	0.4
Section 1	80							



60° Threading Tool - DIN283 - ISO13

Style 166

CODE DESCRIPTION		GRADE		DIM	IENSI0	NS
CODE	DESCRIPTION	GRADE	а	b	L	n
BT245-D014	Right Hand Cutting	P25	10	10	50	5
BT245-D016		P25	12	12	63	6
BT245-D018		P25	16	16	80	8
BT245-D020		P25	20	20	100	10
BT245-D022		P25	25	25	125	12





HSS SQUARE BIT

Sizes
6*6*200mm
8*8*200mm
10*10*200mm
12*12*200mm
16*16*200mm
20*20*200mm



HSS ROUND BIT

Sizes
6*6*200mm
8*8*200mm
10*10*200mm
12*12*200mm
16*16*200mm
20*20*200mm



ROUTER BITS SET




ROUTER BITS SET

8mm shank 6mm shank

(Art No.) : ACBIT1202	2
Cove Box Bit	C x R6.3mm x 9.5mm
Cove Bit	C x R6.3mm x 10mm
Dovetail Bit	C x R6.3mm x 13mm
45° Chamfer Bit	C x 32.0mm x 13mm
Flush Trim Bit	C x 12,7mm x 13mm
Straight Bit	C x 16.0mm x 13mm
Rounding Over Bit	C x R6.3mm x 11mm
Straight Bit	C x 12.0mm x 20mm
Straight Bit	C x 6.0mm x 19mm
Rounding Over Bit	C x R9.5mm x 16mm
90° "V" Grooving Bit	C x 12.7mm x 10mm
Roman Ogee Bit	C x R4.0mm x 12mm

HSS ANNULAR CUTTER

Universal shank, suitable for various magnetic drilling machine; HSS-E with layered and low friction cutting geometry;



SPE	CIFICATION (H	ISS)
12*25mm	20*25mm	30*25mm
13*25mm	21*25mm	32*25mm
14*25mm	22*25mm	34*25mm
15*25mm	23*25mm	36*25mm
16*25mm	24*25mm	38*25mm
17*25mm	25*25mm	40*25mm
18*25mm	26*25mm	
19*25mm	28*25mm	



PILOT PIN 6.34*77mm (25MM)



Applicable to hole drilling and process of annular flute on various magnetic drills and press;



SPE	SPECIFICATION (HSS)						
12*50mm	20*50mm	30*50mm					
13*50mm	21*50mm	32*50mm					
14*50mm	22*50mm	34*50mm					
15*50mm	23*50mm	36*50mm					
16*50mm	24*50mm	38*50mm					
17*50mm	25*50mm	40*50mm					
18*50mm	26*50mm						
19*50mm	28*50mm						












HSS Q COUNTERSINK

HSS-E

Three cutting edges, capacity chip flute Counterbore processing is available Suitable for all kinds of machine tools, electric drill to chamfer







	CODE	SIZE
	TCHQ-306	3-20.5*63*90
SPECIFICATION	TCHQ-307	3-25*67*90
(HSS) (Unit): mm	TCHQ-308	3-31*71*90
	TCHQ-309	3-40*100*90



DOUBLE CUT TUNGSTEN CARBIDE BURRS






(Unit): mm

SPECIFICATION							
CODE	d1	d2	L1	L2	DESCRIPTION		
RB067-D045	6	6	61	16			
RB067-D050	8	6	65	20	Carbide Rotary Burr		
RB067-D055	10	6	65	20	Cylindrical Shape		
RB067-D060	12	6	70	25	With Top Teeth		
RB067-D065	16	6	70	25			



CYLINDRICAL SHAPE WITH TOP TEETH HEAD






(Unit): mm

SPECIFICATION									
DESCRIPTION	CODE d1 d2 L1 L2 DESCRIPTION								
	25	70	6	10	RB067-D330				
Carbide Rotary Burr	28	73	6	12	RB067-D335				
14° Ball Nose Taper Shank	33	78	6	16	RB067-D340				



BALL NOSE TAPER SHAPE





(Unit): mm


		(Viii)			
CODE	d1	d2	L1	L2	DESCRIPTION
RB067-D235	6	6	63	18	
RB067-D240	10	6	65	20	Carbide Rotary Burr
RB067-D245	12	6	70	25	Tree Shape Point End
RB067-D250	16	6	70	25	



TREE SHAPE POINT END

DOUBLE CUT TUNGSTEN CARBIDE BURRS







					(Onit): min
		ΓΙΟΝ			
CODE	d1	d2	L1	L2	DESCRIPTION
RB067-D085	6	6	61	16	
RB067-D090	8	6	65	20	Caulaida Datam Dum
RB067-D095	10	6	65	20	Carbide Rotary Burr Cylindrical Ball Nose
RB067-D100	12	6	70	25	Cyllifurical ball Nose
RB067-D105	16	6	70	25	



CYLINDRICAL BALL NOSE







(Offic): frii									
	SPECIFICATION								
DESCRIPTION	L2	L1	d2	d1	CODE				
Caulaida Datam Dum	18	63	3	6	RB067-D300				
Carbide Rotary Burr Tree Shape Ball Nose	20	65	6	8	RB067-D305				
nee snape ball Nose	32	77	6	12	RB067-D310				



TREE SHAPE BALL NOSE





(Un	it):	mn

					(Unit): mm
CODE	d1	d2	L1	L2	DESCRIPTION
RB067-D125	6	6	50	16	
RB067-D130	8	6	47	20	Carbide Rotary Burr
RB067-D135	10	6	49	20	Cylindrical Shape
RB067-D140	12	6	61	25	With Top Teeth
RB067-D145	16	6	54	25	








BALL SHAPE


SDS DRILL BITS





图

SDS is short for Slotted Drive Shaft or Slotted Drive System. These drills are typically used for heavy-duty drilling into materials such as brick, stone, concrete and other types of masonry. Unlike regular drills, they have a unique design that provides a high level of power during drilling.



CHISELS



CHISELS PLUS SHANK	SPECIFICATIONS				
	POINTED	Ø14mm	400*32mm		
	FLAT	Ø14mm	400*20mm		



CHISELS MAX SHANK	SPECIFICATIONS				
	POINTED	Ø10mm	600*32mm		
	FLAT	Ø18mm	600*25mm		



CHISELS HEX SHANK	SPECIFICATIONS		
	POINTED	ØH28	400 x 32mm
	FLAT	упΖο	400 x 35mm




CHISELS HEX SHANK	SPECIF	ICATION	S
	POINTED	duan	410 x 32mm
	FLAT	ØH30	410 x 35mm





MASONARY DRILL BIT



Description

Industrial Concrete drill bits are hard wearing and are better suited to drilling into harder materials such as concrete. They perform brilliantly when drilling into plaster and brick.


- Profiled tungsten carbide tip

Ace Pro Tip

If holes are drilled beyond the length of the flutes of the drill bit, the bit will lose the ability to clear debris causing it to seize in the hole and may result in damage to the drill bit or drilling machine.

	d	6mm	8mm	10mm	12mm	14mm	16mm	18mm	20mm	22mm	25mm
SIZE	1	400mm	400mm	400mm	400,000	400mm	400mm	400mm	400mm	400mm	400mm
		400111111	400111111	400111111	400mm	150mm	150mm	150mm	150mm	150mm	150mm

SCOTCH EYE AUGER BIT



An auger handle / rod is placed through the eye and the auger is turned by hand to bore.

For boring a wide range of holes in hardwoods in a variety of locations, especially when electrical power is unavailable.


For hand operations

How it works:

A branch or dowel is inserted in the eye of the auger to become the handle to turn the auger drill bit by hand. The handle is not included.

The pilot guide is threaded to "pull" the drill bit into the wood. The cutting edge forms part of the auger helix to assist the drill bit with the removal of shavings.

MASONARY DRILL BIT



Description

Industrial Concrete drill bits are hard wearing and are better suited to drilling into harder materials such as concrete. They perform brilliantly when drilling into plaster and brick.


- Profiled tungsten carbide tip

Ace Pro Tip

If holes are drilled beyond the length of the flutes of the drill bit, the bit will lose the ability to clear debris causing it to seize in the hole and may result in damage to the drill bit or drilling machine.

	d	6mm	8mm	10mm	12mm	14mm	16mm	18mm	20mm	22mm	25mm
SIZE	1	400mm	400mm	400mm	400,000	400mm	400mm	400mm	400mm	400mm	400mm
		400111111	400111111	400111111	400mm	150mm	150mm	150mm	150mm	150mm	150mm

SCOTCH EYE AUGER BIT



An auger handle / rod is placed through the eye and the auger is turned by hand to bore.

For boring a wide range of holes in hardwoods in a variety of locations, especially when electrical power is unavailable.

For hand operations

How it works:

A branch or dowel is inserted in the eye of the auger to become the handle to turn the auger drill bit by hand. The handle is not included.

The pilot guide is threaded to "pull" the drill bit into the wood. The cutting edge forms part of the auger helix to assist the drill bit with the removal of shavings.

HEX SHANK AUGER BIT



HEX SHANK AUGER BIT



SIZE							
d	I						
6mm	200mm						
8mm	200mm						
10mm	200mm						
12mm	200mm						
14mm	200mm						
16mm	200mm						
18mm	200mm						
20mm	200mm						
* 22mm	200mm						
24mm	200mm						
26mm	200mm						

Auger Dill Bit is available in many different sizes according to the requirements of the applications. From small handheld units to large ground bits. An auger bit is primarily used to drill clean holes in a single drilling process. Timber construction, framing, making wooden furniture, gardening, drilling holes for planters, and other professional woodworking jobs require the use of an auger bit.


- Auger drill bits are excellent for drilling a precise hole in wood
- The screw feature allows the removal of wood splatters and dust.
- Perfect for large-scale and industrial woodworking jobs.
- Requires less pressure to drill and withdrawal.
- Auger Bit is perfect for drilling deep holes.
- Minimizes drill jamming or clogging.



BI-METAL HOLESAW SIZE IN MM

BI-METAL HOLESAW





PRODUCT	SET
BIMETAL HOLE SAW	22mm
BIMETAL HOLE SAW	29mm
BIMETAL HOLE SAW	35mm
BIMETAL HOLE SAW	44mm
BIMETAL HOLE SAW	51mm
BIMETAL HOLE SAW	64mm
BIMETAL HOLE SAW	64mm

TWO ARBORS AND DRILL

Bi-Metal	Holesaw
18mm	45mm
20mm	51mm
22mm	60mm
25mm	65mm
27mm	70mm
36mm	92mm

40mm

114mm

Description

Ace craft Hole Saws are made from tough fracture resistant HSS bimetal, ensuring fast accurate cutting and long tool life. They are available in sizes from 14-210mm, with a maximum cutting depth of 32mm for all sizes.

Ace craft Hole Saws give you clean, precise and circular holes in wood, gypsum boards, plastics, non-ferrous metals, aluminium, steel and stainless steel. (Remember to apply even pressure to prevent damage to the teeth.)

Arbors and pilot drills are sold separately for your convenience.

ARBORS FOR METAL HOLE SAWS



SPECIFICATIONS


14 - 30 mm 32 - 152 mm

Description

Arbors are sold separately from Bi-metal Hole Saws.

-Spare pilot centre drill are also available

HSS DRILLS SET, COBALT (M35)



Fully ground HSS Cobalt drill bits manufactured to DIN 338. Cobalt helps to increase the life of the drill bit. 135° Split point enables bits to bite work piece to start drilling.

Efficient clog-free swarf clearance. Suitable for drilling high carbon steel and stainless steel.

SIZES	1	2	3	4	5	6	7	8	9	10	11	12	13
(mm)	1.5	2.5	3.5	4.5	5.5	6.5	7.5	8.5	9.5	10.5	11.5	12.5	

HSS STEEL DRILL BITS



TAPER SHANK DRILL BITS

Sizes (mm)

10	11	12	13	14	15	16
17	18	19	20	21	22	23
24	25	26	27	28	29	30
30.5	32	34	36	38	40	42
50	52	54	56	58	60	62
64	66	68	70	72	75	80
85						



REDUCED SHANK DRILL BITS

Sizes (mm) 13.0*25.0 mm

13.5	14	14.5	15	15.5
16	16.5	17	17.5	18
18.5	19	19.5	20	21
22	23	24	25	



TWIST DRILL BITS

Sizes (mm)

2	2.2	2.5	2.8	3
3.2	3.3	3.5	4	4.2
4.5	4.8	5	5.2	5.5
5.8	6	6.2	6.5	6.8
7	7.5	8	8.5	9
9.5	10	10.2	10.5	11
11.5	12	12.5	13	



HSS STEP DRILL

6 - 30 * 13 mm

6 - 40 * 13 mm

Bright Finish

Laser Markings



LOOSE TAPS & DIES

Taps and dies are tools used to create screw threads, which is called threading. Many are cutting tools; others are forming tools. A tap is used to cut or form the female portion of the mating pair. A die is used to cut or form the male portion of the mating pair.

BSW - British Standard Whitworth

BSP - British Standard Pipe

BSF - British Standard Fine


UNC - Unified Coarse Pitch

UNF - Unified Fine Pitch

THE STATE OF THE PARTY OF THE P				
BSW	BSP	BSF	UNC	UNF
TAPS & DIES	TAPS & DIES	TAPS & DIES	TAPS & DIES	TAPS & DIES
1/4"	1/4"	1/4"	1/4"	1/4"
5/16"	3/8"	5/16"	5/16"	5/8"
3/8"	1/2"	3/8"	3/8"	5/16"
7/16"	5/8"	7/16"	1/2"	3/8"
1/2"	3/4"	1/2"	3/4"	1/2"
9/16"	7/8"	9/16"	1"	Service
5/8"	17	5/8"	# M.	
3/4"	100	3/4"		
7/8"	600	7/8"		70.00
1"	F 5 5 5	1"		
1-1/8"		1-1/8"		
1-1/4"		1-1/4"		

METRIC ISO THREAD


3|4|5|6|8 10|12|14|16|18 20|22|24|30|3



M4*0.35	M8*0.5	M12*1	M18*1.5	M24*1.5
M5*0.35	M10*1.25	M12*1.5	M20*1.5	M24*2
M6*0.75	M10*1	M14*1.5	M20*2	M30*2
M8*1	M12*1.25	M16*1.5	M22*1.5	



DIE STOCK



ZINC 16X5	ZINC 30x11
ZINC 20x5	ZINC 38x10
ZINC 20x7	ZINC 38x14
ZINC 25x9	ZINC 45x14

ZINC 55x16 Z	ZINC 65x18
ZINC 55x22	

*lxd

RATCHET TAP WRENCH




with level No.1	C45 M3-M10
with level No.2	C45 M5-M12

MORSETAPER SLEEVES



SPECIFICATION (DIN2185)		
SLEEVE	TAPER	
MORSE TAPER SLEEVE	MT1	MT0
MORSE TAPER SLEEVE MT2 MT1		MT1
MORSE TAPER SLEEVE	DRSE TAPER SLEEVE MT3 MT2	
MORSE TAPER SLEEVE	RSE TAPER SLEEVE MT4 MT3	
MORSE TAPER SLEEVE MT5 MT4		MT4
MORSE TAPER SLEEVE	MT6	MT5

Precision execution, completely hardened. Internal and external taper grounded according DIN 2185



CENTER DRILL BITS

1.1.			Unit): mm	
SPECIFICATION				
CENTER DRILL	d1	d2	L1	L2
CENTER DRILL #2	4.76	1.98	1.98	48
CENTER DRILL #3	6.35	2.78	2.78	51
CENTER DRILL #4	7.94	3.18	3.18	54
CENTER DRILL #5	11.11	4.76	4.76	70
CENTER DRILL #6	12.70	5.56	5.56	76



32 PIECE METRIC TAP & DIE SET

Features: Internal and external threads cutting tools matched in one

box with GSR patened tool holders

Standard: DIN352/DIN1814/DIN225/Factory standard

Material: HSS M2 Range: M3-12

Contents:

21pcs taps DIN352 3pcs set,M3-4-5-6-8-10-12 No.1-2-3
7pcs dies 25x9,Factory standard,M3-4-5-6-8-10-12

1pc die holders DIN225,25x9mm, GSR patented
1pc tap wrenches DIN1814,No.1.1/2(M1-12), GSR patented

1pc pitch gauge 14S,internal & external threads gaug,GSR patended

1pc screw driver





45 PIECE METRIC TAP & DIE SET

- Made from high speed steel (HSS)
- 40 Metic taps & dies, fine & coarse:
- M6x1.0, M6x0.75, M8x 1.25, M8x1.0
 M10x1.5, M10x1.25, M12X1.75, M12X1.5,
 M14X2.0, M14x1.5, M16x2.0, M16x1.5,
 M18x2.5, M18x1.5, M20x2.5, M20x1.15,
 M22x2.5, M22X1.5, M24X3.0, M24X1.5
- Includes: Die handle 2 "OD, Tap wrench & T-type tap wrench



54 PIECE METRIC TAP & DIE SET

Features: Internal and external threads cutting tools matched in

one box, with GSR patened tool holders

Standard: DIN352/DIN223/DIN1814/DIN225

Material: HSS M2 Range: M3-20

Contents:

33pcs taps DIN352 3pcs set,M3-4-5-6-8-10-12-14-16-18-20 No.1-2-3

11pcs dies DIN223/ISO22568,M3-4-5-6-8-10-12-14-16-18-20 6pc die holders DIN225, 20x5-20x7-25x9-30x11-38x14-45x18mm,

2pc tap wrenches DIN1814,No.1(M1-10)-No.3(M5-20),GSR patented

2pcs ratchet holder No.1(M3-10)-No.2(M5-12)

1pc pitch gauge 20S

1pc screw driver





64 PIECE METRIC TAP & DIE SET

Features: Internal and external threads cutting tools matched in

one box, with GSR patened tool holders

Standard: DIN352/DIN223/DIN1814/DIN225

Material: HSS M2 Range: M3-24

Contents:

39pcs taps DIN352 3pcs set,M3-4-5-6-8-10-12-14-16-18-20-22-24 No.1-2-3

13pcs dies DIN223/ISO22568,M3-4-5-6-8-10-12-14-16-18-20

7pc die holders DIN225, 20x5-20x7-25x9-30x11-38x14-45x18-55x22mm,

3pc tap wrenches DIN1814,No.0 (M1-8)-No.1(M1-10)-No.3(M5-20),GSR patented

1pc pitch gauge No.1(M3-10)-No.2(M5-12)

1pc screw driver 20S M/Ww



ARMATURE & CARBON BRUSH





CARBON BRUSH

PRODUCT	SPECIFICATIONS
Carbon brush	CB HIT 021(brush)
Carbon brush	CB HIT 061(brush)
Carbon brush	CB HIT 038(brush)
Carbon brush	CB MET 177(brush)
Carbon brush	Dewalt 9" 16.0 * 4.0 * 24.0mm
Carbon brush	Dewalt 4.5"
Carbon brush	Black and decker 4.5"
Carbon brush	FERM 9"
Carbon brush	FERM 4.5"

BROACHES



#70, wooden box packing

Keyway combinations 26

No. 70 Metric Set EDP No. 44498	Keyway Sizes	Broach Style	Bushing Diameters (Bore Sizes)
Our most popular metric Broach Set.	4,5	B1	12, 14, 15, 16
4 Broaches and 13 Bushings $=$ 26 keyway combinations.	6,8	С	18, 19, 20, 22, 24, 25, 26, 28, 30
Collared B1 and C Bushings	,		


FLOOR TYPE DRILL **PRESS**


DRILL PRESS ACPD120

20mm Floor Type Drill Press

- 3/4" (20mm)Max. Capacity
- 325mm swing
- 16 Spindle Speeds
- -45°~0°~+45° Table Tilt L&R
- Optional Chuck Guard And Micro-switch For CE Requirement

	MODEL	ACPD120
Α	Max Drilling Diameter(mm)	Φ20mm(3/4")
	Motor Power	450/550/750W
	Chuck Capacity(mm)	5-20
В	Spindle Travel(mm)	80
	Class Of Speed	16
inn.	Speed 50/60Hz	180~2770/220~3320R.P.M.
C	Spindle Taper	MT2
D	Max. distance from spindle axis to surface of column(mm)	162.5
E	Max. distance from spindle end to surface of table(mm)	725
F	Max. distance from spindle end to surface of base(mm)	1205
	Swing(mm)	325
	Table Size(mm)	250X250
	Base Size(mm)	460X270
G	Column Diameter(mm)	Φ72
Н	Height(mm)	1580
	Net Weight/Gross Weight(kg)	57/60
	Packing Size(mm)	1110X450X275

















BENCH GRINDERS

BENCH GRINDER - MD3215



BENCH GRINDER - MD3220



BENCH GRINDER - MD3225



SPECIFICATIONS		
Size	150*25*31.75mm	
Power	0.25Kw	
Voltage	220V	
Current	1.9Amp	
Speed	2850 R/MIN	
Frequency	50Hz	

SPECIFICATIONS		
Size	200*25*31.75mm	
Power	0.5Kw	
Voltage	220V	
Current	2.66Amp	
Speed	2850 R/MIN	
Frequency	50Hz	

SPECIFICATIONS		
Size	250*25*31.75mm	
Power	0.75Kw	
Voltage	220V	
Current	2.90Amp	
Speed	2850 R/MIN	
Frequency	50Hz	

PEDESTAL GRINDER

Size	300*40*75mm
Power	1.5Kw
Voltage	380V
Current	3.4Amp
Speed	1420 R/MIN
Frequency	50Hz



DESCRIPTIONS		
GS,CE, EMC		
Voltage/Frequency	210-240V, 50/60HZ	
Input power	2400w	
Blade Dia.	355mm	
No-Load Speed	3600r/min	
G.W./N.W.	20/18.5kgs	
Package size	60x35.5x44.5cm/pc	
Bore	30mm	
CUTTING CAPACITY		
Bar(Dia.)	51mm	
Pipe(Dia.)	130mm	
Rectangle	220 x 85mm	
Square	115 x 115mm	
Right angle	135 x 135mm	



DESCRIPTIONS				
Voltage/Frequency	110-240V, 50/60HZ			
Input power	1800w/15A			
Blade Dia.	305mm			
No-Load Speed	3250r/min;			
G.W./N.W.	16/14kgs			
Package size	79x48x40cm/pc			
CUTTING CAPACITY				
Miter x Bevel	Width x Height(mm)			
0° x 0°	305 x 70			
45° x 0°	210 x 70			
0° x 45°	305 x 35			
45° x 45°	210 x 35			

blade, Hex key screwdriver, clamp, dust collector, extension bar



ACCESSSORIES

blade, Hex key screwdriver, clamp, dust collector, extension bar, laser

DESCRIPTIONS				
G	S,CE,EMC,ETL			
Voltage/Frequency 110-240V, 50/60HZ				
Input power	2000w/15A			
Blade Dia.	255mm			
No-Load Speed	110-120V, 5200r/min; 220- 240V, 5500r/min			
G.W./N.W.	25/21kgs			
Package size	88x56x44cm/pc			
CUTTING CAPACITY				
Miter x Bevel	Width x Height(mm)			
0° x 0°	340 x 80			
45° x 0°	240 x 80			
0° x 45°	340 x 50			
45° x 45° 240 x 50				



blade, Hex key screwdriver, clamp, dust collector, extension bar

DESCRIPTIONS						
(GS CE EMC					
Voltage/Frequency	110-240V, 50/60HZ					
Input power	1500w/15A					
Blade Dia.	210mm					
No-Load Speed	3250r/min;					
G.W./N.W.	16/14kgs					
Package size	79x48x40cm/pc					
CUTTING CAPACITY						
Miter x Bevel	Width x Height(mm)					
0° x 0°	220 x 70					
45° x 0°	155 x 70					
0° x 45°	220 x 35					
45° x 45°	155 x 35					



blade, Hex key screwdriver, clamp, dust collector

DESCRIPTIONS				
Voltage/Frequency 110V-240V, 50/60HZ				
Input power	1800W			
Blade Dia.	250m, 24T			
No-Load Speed	5000r/min			
G.W./N.W.	32/21kgs			
Package size	91 x 75 x 37cm/pc			
Table Size	650×570×28mm			
Cutting range	0-45 degree			
Table width extention	Right 635mm			
Cutting height max	80mm@90°, 60mm@45°			
Dust Pot	32mm			
Operate Height	850mm			
Height adjustment	0-80mm			



ACCESSSORIES

High pressure spray gun with ajustable spray nozzle 5 Meter High pressure hose Foam bottle HPC connector with filter 5 meter power cable with plug

DESCRIPTIONS				
Voltage/Frequency	110V-240V, 50/60HZ			
Input power	1400W			
Reated pressure 7MPa(70bar)				
Max. pressure	10.5MPa(105bar)			
Flow rate	5.5L/min			
Max. flow rate	6.8L/min			
N.W.	6.5kgs			
G.W.	7.0kgs			

MAGNETIC BASE DRILLING MACHINE

MAGNETIC BASE DRILLING MACHINE MB355

Magnetic core drilling machine is a portable drilling machine with a magnetic base. It can use twist drill bits, annular cutters, milling cutters, and other rotary cutters. Magnetic drilling machines with reversible motor and variable speed controls can also perform operations like tapping, countersink, and reaming.

FUNCTION DESCRIPTION			
Variable Speed	Strong adhesion		
Core Drill	Chuck: 13mm		
Overload Protection	ChuckAdaptor		
Carbon Brush	Mount: 1/2" UNF		
Torque Control	Safety Strap		
Inner Lubrication Light weight			

TECHNICAL SPECIFICATIONS				
Core Drilling Dia.	Ø 35 mm			
Annular Cutter	12 - 35 mm			
Twist Drilling	1 - 13 mm			
Rated Voltage	110/220V			
Rated Frequency	50 -60 Hz			
Rated Input Power	1550 W			
No-Load Speed	100-830 Rpm			
Magnet Adhesion	14800 N			
Cutting Depth	30 mm			
Stroke	120 mm			
Cable Length	2.5 mm			
Magnetic Dimension	166 x 80 x 50 mm			
Packaging Size	580 x 380 x 180 mm			
Net / Gross Weight	12 / 15 mm			







MAGNETIC BASE DRILLING MACHINE MB980

The magnetic drill relies on the adsorption force of the magnetic base to perform drilling operations from different angles. Because of its small size and high power, it is extremely efficient. The magnetic drill solves the problem of removing waste and slag from pipelines and drilling holes in steel plates.

FUNCTION DESCRIPTION			
Built-in cooling system	Strong adhesion		
Core Drill	Alloy Frame		
All die-cast magnesium	ChuckAdaptor		
Carbon Brush	Plastic box + Carton		
Torque Control	Alloy Frame		
Inner Lubrication	Light weight		

TECHNICAL SPECIFICATIONS				
Rated Voltage	100 / 220 V			
Rate Frequency	50/60 Hz			
Rated Inputted Power	2180 W			
Max Drilling	98 mm			
Twist Drill Range	28 mm			
Magnet Adhesion	17000 N			
No-Load Speed	100-380 Rpm			
Stroke Length	180 mm			
Max Depth	80 mm			
G.W.	31 kgs			
N.W.	25 kgs			
Packing Dimension	450 x 210 x 460 mm			



Core drill: ø 98 mm L 50 mm



Twist drill: ø 28 mm



ICeM (THREADING AND GROOVING)

I/2" - 2" INOUSTRY QUALITY

Manual Ratchet Threaders

HL-I2R

Product Description

 All matched Threader/Sets including Die Heads, Ratchet Assembly. Ratchet and Alloy Dies. Different Threaded Sets maybe use different Dies and Head, consult us when you are choosing.

Ratchet Lever

- Convenient. lockable reversal of ratchet direction
 Quick adjustment
- Secure hold with retainer locking, simple insertion, and removal of die heads

User friendly

• Slim compact shape with excellent overall size, angle requirements of 22.5'

For easy work in difficult to reach positions

 Ratchet Assembly and long lever Labor-saving

Quick Change Die Heads

• Positive octagonal universal drive with retainer locking

Secure/hold

Long pipe guide

Perfect cantering

Simple insertion and removal of die heads


Easy changing

Precision Dies

- High-quality tempered steel
- Optimised cutting geometry

Ordering Information

Catalo	Catalog No.		Сар	acity	N.W
BSPT	NPT	Model No.	in.	mm	kg
602210	602209	HL-12R	<i>У</i> ₂−2	12-50	25





PRODUCT	SET
Spare Dies for 12 R	1/2"
Spare Dies for 12 R	3/4"
Spare Dies for 12 R	1"
Spare Dies for 12 R	1 1/14"
Spare Dies for 12 R	1 1/2"
Spare Dies for 12 R	2"

ICeM (THREADING AND GROOVING)



Manual Ratchet Threaders

HL-63

Ordering Information

Catalo	og No.	Capacity		N.W	
BSPT	NPT	Model No.	in.	mm	kg
4511310	4511311	HL-63	3/8-2	10-50	12.5
4511312	4511313	HL-63	½-2	12-50	12

PIPETHREADING MACHINE



Capacity

- Pipe: ¼" -2" (18mm-50mm)
- Bolt: 12mm-45mm

Features

- Heavy.duty proven performance.
- 1.5KW induction motor ensures quiet operation with high speed.
- Self-Contained Oil System constant flow
- Approved by CSA and CE standards.

Technical Specifications

- Motor: 1500W induction. 50/60Hz
- * Switch : ON/OFF heavy duty switch, footswitch and FOR/OFF/REV switch are optimal
- Spindle Speed: 38 RPM.
- Front Chuck : Hammer type with replaceable rocker action jaw inserts.
- Rear Centering Device : Cam action.
- Oiling System: Through die head, with integral oil reservoir.

LADDER5





TELESCOPIC LADDER

SPECIFICATIONS		
No. of steps	11	
Length	4.2 m	
Max Load	150kg	
Material	Aluminium	
Weight	15kg	



EXTENSION LADDER

SPECIFICATIONS		
No. of steps	2*10	
Length	5.72 m	
Max Load	150kg	
Material	Aluminium	
Weight	11.3kg	



R-FRAME LADDER

SPECIFICATIONS		
No. of steps	2*9	
Length	3 m	
Max Load	150kg	
Material	Aluminium	
Weight	12kg	



COMBINATION LADDER 4X4

SPECIFICATIONS		
No. of steps	16	
Length	4.4 m	
Max Load	150kg	
Material	Aluminium	
Weight	15kg	






CHAINSAW CHAIN



LENGTH	PITCH	GAUGE	DRIVE LINKS
15"	3/8"	0.058"	56DL
18"	3/8"	0.058"	68DL

CHAINSAW GUIDE BAR



LENGTH	
15"	*to fit
18"	*to fit

to fit saw chain 3/8"-.058"-56DL

*to fit saw chain 3/8"-.058"-68DL

CHAINSAW FILE

Thickness:4.8mm



TRIMMER LINE

THICKNESS	LENGTH
3.0mm	10M
3.0mm	240M



2024 PRODUCT

CATALOGUE

INDUSTRIAL SOLUTIONS

CUTTING TOOLS | ABRASIVE SOLUTIONS | FLUID HANDLING

HARARE

35 Coventry Road, Workington +263242754030 | +263242753319 acehardware@acehardware.co.zw

MUTARE

10B Riverside Drive +2632064503 | +263774470944 | +263776977117 acesales3@acehardware.co.zw

BULAWAYO 104 Fife Street +26329265171 | +26329263731 byosales@acehardware.co.zw

